


Flexible Conveyors

Flexible
Self Tracking
Modular & Expandable
Motorized/ Gravity
Adjustable Height



Alstrut's **Flexible Conveyors** are a must have in any production line or warehouse. These conveyors are suitable for environments with changing material handling conveying requirements. They are ideally suited to convey part bins, carton boxes or parcels.

The Flexible Conveyors can be collapsed together to make it into a smaller length conveyor. Depending on requirement, they can be stretched to form a longer conveyor which could increase in length over twice the collapsed length.

In a stretched condition, the conveyors can also be twisted or turned, enabling moving of parts between two points which may not be in a straight line. The ability to increase or decrease the heights at each end of the conveyor enables transfer of products between two different heights.

The Flexible Gravity Roller Conveyor and Skate Wheel Conveyor are most efficient for pushing the product, or, letting products move by gravity. The Flexible Motorized Roller Conveyor are suited for conveying parts over longer distances without the need for operator efforts. All conveyors come with options of different widths and roller diameters depending on the application.

- Rapid Loading & Unloading in Warehouse
- Suitable for Handling all Kinds of Products
- Simple, Reliable & Safe Operation
- Increases Throughput
- Reduce Labor Fatigue
- Increase Efficiency

eatures

- Economical
- Flexible & Expandable
- Self Tracking
- Movable
- Turn/ Twist
- Low Maintenance
- Adjustable Height/ Length

Specifications

		Expanded Length			Compressed Length				
Series	Conveyor Type	First Section	Middle	Last Section	First Section	Middle	Last Section	Load Capacity	Adjustable
		(mm) A	Section (mm)	(mm) C	(mm) X	Section (mm)	(mm) Z	(Kg/Section)	Speed
AF-01	Motorized	1,100	1,000	1,100	450	400	450	40	10 - 18
AF-02	Gravity (Zinc Plated Steel)	1,250	1,100	1,250	560	460	560	50	-
AF-03	Gravity (Double Roller) Plastic / Steel	1,250	1,100	1,250	540	420	540	40	-
AF-04	Skate Wheel (Galvanized Steel)	1,250	1,100	1,250	430	340	430	40	-
AF-05	Skate Wheel (Plastic)	1,250	1,100	1,250	430	340	430	40	-

Width (mm)	600 mm			
Adjustable Height	700 mm - 1,000 mm			

To Calculate Length of Conveyor:

Expanded Length (Basis for Ordering)

A + B * n + C

Compressed Length (For Information)

X + Y * n + Z

where n are the number of middle sections



Machine Building Components Assembly Line & Workplaces Material Handling Solutions Robotic Solutions Special Purpose Machines



www.alstrut.com

Alstrut India Private Limited 267 Kilpauk Garden Road

Chennai 600 010, India